




Excel NR™ Floor System

SYSTEM TYPE: FLOATING RESILIENT



Double Plywood Subfloor Comprised of 15/32" (12 mm)

Action AirTech 7/16" (11 mm) Natural Rubber Pads

MFMA NORTHERN HARD MAPLE BY ACTION:

Random Length (RL)
Action Long Length (FJ)

TESTING AGENCY:

Certified by ISSS

PERFORMANCE MEETS OR EXCEEDS:

EN 14904 Type 4
DIN 18032 Part 2
ASTM - F2772
MFMA PUR
FIBA Level I

SLAB DEPRESSION:

25/32" (20 mm): 2-1/8" (54 mm)
33/32" (26 mm): 2-3/8" (60 mm)

LEED:

FSC Maple & Subfloor available, MR credits — based on products, selected materials and facility locations


PERFORMANCE & SYSTEM STABILITY:

- Factory fabricated
- Excellent ball bounce
- SCORES Compliant
- Stable double layer plywood subfloor system
- Excellent shock absorption

- Innovative design that achieves outstanding playing performance characteristics in a floating floor system.
- Factory fabricated subfloor provides a level of consistency and uniformity on the installed system maximizing performance and satisfaction.
- The manufacturer and flooring shall be independently verified by the guidelines of the ISO 14040-2006 and ISO 14044: 2006 Life Cycle Assessment (LSA) confirming a negative carbon footprint.
- Carbon Evaluation must be inclusive and based on all corporate facilities, offices and mills.
- The manufacturer and flooring shall be independently verified by the guidelines of the ISO 14064-1:2006 World Resource Institutes Greenhouse Gas Protocol, Scope 1, 2 and 3.
- The manufacturer and flooring shall be registered in the Collaborative for High Performance Schools (CHPS) Product Database.

Complete product specifications and system drawings (CAD and BIM) are available online at:

www.actionfloors.com



Action Excel NR



ACTION FLOOR SYSTEMS LLC
4781 N. U.S. Hwy. 51 • Mercer, WI 54547-9708 U.S.A.

PHONE: 800.746.3512 or 715.476.3512 • FAX: 715.476.3585
E-MAIL: info@actionfloors.com

www.actionfloors.com

